INCIDENT RADIO COMMUNICATIONS PLAN			Incident Name			Date/Time Prepared		Operational Period Date/Time		
			WinterWeather Event Jan 2-3, 2014			January 2-3, 2014		1-2-14 2200 - 1-3-14 0800		
Ch #	Function	Channel Name/Trunked Radio System Talkgroup	Assignment	RX Freq N or W	RX Tone/NAC	TX Freq N or W	Tx Tone/NAC	Mode A, D or M	Remarks	
1	HF Voice	Central Area	Daytime	7.2505				Α	LSB	
2	HF Voice	Central Area	Night	3.9935				Α	LSB	
3	HF Voice	Eastern Area	Daytime	7.2275				Α	LSB	
4	VHF Voice	Eastern Area	Night	3.9875				Α	LSB	
	VHF Voice	Western Area	Daytime	7.2720				Α	LSB	
5	VHF Voice	Western Area	Night	3.9905				Α	LSB	
6	LSB Data	PaNBEMS		3.583				D	Olivia 1500Hz 8/500	
7	LSB Data	PaNBEMS		7.0730				D	Olivia 1500 Hz 8/500	
8										
9										
10										
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										
Prepared By (Communications Unit) Incident L						tion Statewide				
Susan Singer, KB3KDC, PEMA ACS Coordinator					County St	County State Latitude Longitude				

The convention calls for frequency lists to show four digits after the decimal place, followed by either an "N" or a "W", depending on whether the frequency is narrow or wide band. Mode refers to either "A" or "D" indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.

ICS 205 Excel 3/2007